

CODE: 07.930E-08-0
THESE DATA ARE CONFIDENTIAL AND THE PROPERTY OF IPIP-S.A. AND SHALL NOT BE DISCLOSED TO OTHERS OR PRODUCED IN ANY MANNER FOR PURPOSE NOT PROVIDED BY AGREEMENT, UNLESS THE WRITTEN PERMISSION OF IPIP-S.A.

ipip		PROJECT SPECIFICATION		NO. 1168.00-36-6024.PS			
JUNCTION BOX		SHEET 3 OF 4					
ITEM	DENOMINATION	DESCRIPTION	QUANTITY (pcs/kg)				NOTES
			Rev.0	Rev.1	Rev.2	Rev.3	
SYMBOL : JUNCTION BOX							
1	JUNCTION BOX	Approved for:	2	4			1
2		- Ex II 2 G EExd IIB T4					
3		External paint:					
4		- Mfr. Std.					
5		Internal paint:					
6		- Mfr. Std.					
7		Protection degree:					
8		- IP66					
9		Tag plate:					
10		- From stainless steel					
11		Cable glands for individual cables:					
12		- Inlet: 6 pcs. (Ex d Locknut M20 Brass)					
13		- Outlet: 1 pcs. (Ex d Locknut M32 Brass)					
14		DIN rail:					
15		- 1pcs.					
16		Terminal strips (screw-antiloosing type for DIN rail mounting) suitable for wire with cross section between 1-1.5 sqmm					
17		Will be provided with:					
18		- Earthing cables armour to ground					
19		- Bracket for wall/pilar mounting					
20							
21							
22		Tag No. 20-JB-AI-003					
23		20-JB-AI-004					
24		20-JB-AI-005					
25		20-JB-AO-001					
26							
27							
28							
29							
30							
REV. 0 = FIRST MATERIAL TAKE-OFF			REFERENCE DOCUMENTS :				
ANY REFERENCE TO THESE MATERIALS MUST BE BY SHEET AND ITEM NUMBER							
NOTES : 1. Ambient temperature limits: min. -26.6°C , max. +39.9°C							

PLK