

MICROMASTER 4 BRAKING RESISTOR 380-480 V 27R 24000 W  
PK 1200 W CONT 515 X 270 X 175 MM H X W X D IP20



Figure similar

Order number	
Phase number / of the input voltage	Wert fehlt!
Type of voltage / of the input voltage	Wert fehlt!
Input voltage	Wert fehlt! ... Wert fehlt!
DC link voltage	900
Consumed active power / rated value	1.2 kW
• maximum	24 kW
Type of electrical connection / for power cable	M6 screw studs
Connectable conductor cross-section / for power cable	6 mm <sup>2</sup>
Design of the temperature switch	Normally closed contact
Input voltage / of the temperature switch / at AC / maximum	Wert fehlt!
Input current / of the temperature switch / at AC / maximum	2.5 A
Connectable conductor cross-section / on the temperature switch / maximum	2.5 mm <sup>2</sup>
Type of electrical connection / of the protective conductor connection	M6 screw studs

Design of the protective conductor connection / on enclosure	M6 screw studs
Protection class IP	IP20
Electrical resistance / of the braking resistor	27 $\Omega$
Width	270 mm
Height	515 mm
Depth	175 mm
Net weight	7.4 kg

#### Further information

##### Information und Download Center

[https://www.automation.siemens.com/mcms/infocenter/content/en/Pages/order\\_form.aspx](https://www.automation.siemens.com/mcms/infocenter/content/en/Pages/order_form.aspx)

##### Technical documentation

<http://w3.siemens.com/mcms/mc-solutions/en/motion-control/support/technical-documentation/Pages/technical-documentation.aspx>

##### Industry Mall

<https://eb.automation.siemens.com/mall/en/WW/Catalog/Product/6SE6400-4BD21-2DA0/all>

##### Industry Online Support

<http://support.automation.siemens.com/WW/view/en/6SE6400-4BD21-2DA0/all>