





Aproved by: P. Vlăsceanu

Checked by: V. Bologa 🐇

Prepared by: A. Boscornea

Construction of Sulfur Recovery Unit 3

PROCESS DATA SHEET

Water Spray Nozzle 304-X-101

Project Phase: DTDE

Project No.: 1267PJ

Client: S.C. PETROTEL - LUKOIL S.A.

Site Location: Ploiești, Prahova, Romania



	Revision	Date	Revision description
	0	19.03.2020	First Issue
_			
I-REV.3.1			
11-RI			
002-F			
WP-UE1-002-F11			
WΡ			



2) Typical configuration. To be confirmed by Vendor. 3) Vendor will include spare parts and consumables for 2 years operation.		1. DESIGN DA	ATA	R
pire ystem flow into the bottom eaction of the contact condenser column via. 13 meters of DN600 Stainless Sixel duci and 3 elbows. Target diopet size: 200 micro.os. Vater pressure a fit a 53 C. NOR Piter (Sour vater). Cutef pressure in a 20 contact for the state of the state of the valuable vater in the state of the valuable vater in the valuable state of the valuable vater in the v				
Water forw 7m ² /m it 03 °C. DNB0 Pipe (Sour water). Image diophilises 200 microns. Image diophilises 200 microns. Water preserve at nozzle inition for sole 30 brang. Image diophilises 200 microns. Image diophilises 200 microns. Counter frow with angle type III cone nozzle (Note 1). Image diophilises 200 microns. Image diophilises 200 microns. Nazzle is be withdrauble without hubiting down the process. At or nihrogen purging is available. Vendor to advise method. Image diophilises 200 microns. Nazzle is proteined form biologies by double infine atrainers. Vendor to advise method. Image diophilises 200 microns. Master at Topper track (Mormal Operating Conditions) Image diophilises 200 microns. Image diophilises 200 microns. Ownede kingh 1188 5000 Image diophilises 200 microns. Instance Kingh 138 diophilises 200 microns. Image diophilises 200 microns. Instance Kingh 138 diophilises 200 microns. Image diophilises 200 microns. Instase contig </td <td></td> <td></td> <td></td> <td>water from the</td>				water from the
Target depict size: 200 microns. Order pressure in process gaine: 0.05 harg. Conterf-row with angle byte Uit core notice (Note 1). Nazzis to be withdrawable withouth shutting down the process. Air or ninogan purging is available. Vendor to advise method. Nazzis to be withdrawable withouth shutting down the process. Air or ninogan purging is available. Vendor to advise method. Nazzis to be withdrawable withouth shutting down the process. Air or ninogan purging is available. Vendor to advise method. Design Temperature: 375 C. Material: 3116. SD. Case Stream Properties (Normal Operating Conditions) Invariab kg/h 11855.000 tass Finovrabe kg/h 388.800 tass Finovrabe kg/h 388.800 tenstrating Kg/m 3 0.500 tass Density kg/m 3 0.500 tass Density kg/m 3 0.500 tass Density kg/m 3 0.500 tass Density kg/m 3 0.500 tass Density Kg/m			eters of DN600 Stainless Steel duct and 3 elbows.	
Water prosessing at in 2021e Initia 4.5 hard. Image: Solution of Solution 10. Counter-flow with angle byte full core nozzle (Note 1). Image: Solution 10. Nazzle is protected form blockage by double initine strainers. Vendor to advise mesh size. Image: Solution 10. Design Temperature: 375 °C Image: Solution 10. Image: Solution 10. Materia: 1314. SS. Image: Solution 10. Image: Solution 10. Gas Stream Properties (Normal Operating Conditions) Image: Solution 10. Image: Solution 10. Image: Solution 10. KPA (g) -0.000. Image: Solution 10. Image: Solution 10. KPA (g) -0.000. Image: Solution 10. Image: Solution 10. KPA (g) -0.000. Image: Solution 10. Image: Solution 10. KPA (g) -0.000. Image: Solution 10. Image: Solution 10. KPA (g) -0.000. Image: Solution 10. Image: Solution 10. KPA (g) -0.000. Image: Solution 10. Image: Solution 10. KPA (g) -0.000. Image: Solution 10. Image: Solution 10. KPA (g) -0.000. Image: Solution 10. Image: Solution 10.		e (Sour water).		
Outer process gas line : 0.56 barg. Contendew with angle type full concerned (Note 1). Naczle to be withdrawafia withouth shutting dawn the process. Air or ningen purging is available. Vendor to advise method. Naczle to be withdrawafia withouth shutting dawn the process. Air or ningen purging is available. Vendor to advise method. Naczle to be withdrawafia withouth shutting dawn the process. Air or ningen purging is available. Vendor to advise method. Naczle to be withdrawafia withouth shutting dawn the process. Air or ningen purging is available. Vendor to advise method. Design Temperature: 375 °C. Maderat: 316.35. Naczle to be shutting dawn the process. Air or ningen purging is available. Gas Steam Properties (Normal Operating Conditions) Image and the shutting dawn the process of the shutting dawn the process of the shutting of the shutting dawn the process of the shutting dawn the shutting dawn the shutting dawn the process of the shutting dawn the shutting dawn the process of	•			
Canther.fow with angle type full cone nozzle (Notes 1). Construction to with angle type full cone nozzle (Notes 1). Nozzle to be withdrawable withdni have burling down the process. At or nitogan punging is available. Vendor to advise method. Nozzle to be withdrawable withdni have burling down the process. At or nitogan punging is available. Vendor to advise method. Nozzle to be withdrawable withdni have burling down the process. At or nitogan punging is available. Vendor to advise method. Nozzle is provented from blockáge by double inline strainers. Vendor to advise mesh size. Design Transportation: 75 burg. Naterial: 1816. SA. Gas Stream Properties (Normal Operating Conditions) withdrawable withdni At 11885.000 with a sa Flowrate withdrawable withdni At 11885.000 with a sa Flowrate withdrawable withdni At 11885.000 with a sa Flowrate withdrawable at the same at the				
Nazik bio withdrawebia withouth shufung down the process. Ar or nitegon purging is available. Vendor to advise method. Design Pressure: 7.5 barg. Design Pressure: 7.5 b				
Nazzie is protecked form blockage by double infine strainers. Vendor to advise mesh size. Design Pressure: 75 Brag. Image: 15 Brag. Dasign Temperature: 375 °C. Image: 15 Brag. Gas Stream Properties (Normal Operating Conditions) Image: 15 Brag. Iowrate kg/h 11085:00 are Flowrate kg/h 11085:00 Image: Stream Properties (Normal Operating Conditions) Image: 15 Brag. Image: 15 Brag. Image: Stream Properties (Normal Operating Conditions) Image: 15 Brag. Image: 15 Brag. Image: Stream Properties (Normal Operating Conditions) Image: 15 Brag. Image: 15 Brag. Image: Stream Properties (Normal Operating Conditions) Image: 15 Brag. Image: 15 Brag. Image: Stream Properties (Normal Operating Conditions) Image: 15 Brag. Image: 15 Brag. Image: Stream Properties (Normal Operating Conditions) Image: 15 Brag. Image: 15 Brag. Image: Stream Properties (Normal Operating Conditions) Image: 15 Brag. Image: 15 Brag. Image: Stream Properties (Normal Operating Conditions) Image: 15 Brag. Image: 15 Brag. Image: Stream Properties (Normal Operating Conditions) Image: 15 Brag. Image: 15 Brag. Image: Stream Prop				
Design Fressure 7.5 bar. Opering Temperature 737 °C. Material: 316L 95. Gas Stream Properties (Normal Operating Conditions) Ownate kmol/h 473.300 Itss Flowrate kg/h 11866.000 Itss Flowrate kg/h 11866.000 merenture 1C 338.800 Tessure (rimi) kPa (g) -0.500 Itsa branky kg/m08 0.500 Tass Darsky kg/m08 0.500 Tessard Capacity KMr H 0.028 Innema Conductivity W/m K 0.028 Innematic Viscosity CSR 59.262 Vardor. 2 DRAWINGS AND SKETCHES V Verdor. 3.NOTES 1 1 1 1 <td></td> <td></td> <td></td> <td></td>				
Design Femperature 375 Q. Material: 316L SS. Gas Stream Properties (Normal Operating Conditions) lowrate knowled knowled 473.300 tass Flowrate kQh 11885.000 emperature C 338.800 emperature C 300 Ease Flowrate C 338.800 emperature C 300 Ease Flowrate C 3000 Ease Flowrate C 3000 Ease Flowrate C 3000 Ea		louble inline strainers. Vendor to advise mes	h size.	
Material: 318L SS. Gas Stream Properties (Normal Operating Conditions) Image: Condition of the stress of the stre	Design Pressure: 7.5 barg.			
Gas Stream Properties (Normal Operating Conditions) 473.300 1 Iowrate kg/h 11886.000 1 msperature C 338.800 1 msperature No 308.800 1 1 msperature C 338.800 1 1 msperature Kg/m3 0.500 1 1 1 tass Density Kg/m3 0.500 1 1 1 tass Density Kg/m3 0.500 1 </td <td>Design Temperature: 375 °C.</td> <td></td> <td></td> <td></td>	Design Temperature: 375 °C.			
iowrate km/h 473.300 lass Flowrate kg/h 11885.000 mperature C 338.800 ressure (rim) kPa (g) 0.500 M 39447.7 1 W kg/kmole 25.100 Jass Density kg/mole 25.100 Jass Density kg/kmole 25.100 Jass Hat Capacity kJkg K 1.314 Hermal Conductivity W/m K 0.050 Jass Hat Capacity cP 0.029 Inematic Viscosity cSt 59.262 Vendor. - -	Material: 316L SS.			
lass Floryzate lg/h 11865.00 Image: second control of the second conte second control of the second conte second control of	Gas Stream Properties (Normal Opera	ting Conditions)		
emperature C 338.800 ressure (min) kPa (g) -0.500 minalty MJh -39447.7 W kg/kmole 25.100 Base Density kg/m3 -0.500 Itase Itas Zapacity kJKg/K 1.314 hermal Conductivity Wim-K -0.029 inematic Viscosity oP -0.029 inematic Viscosity cSt 59.262 inematic Viscosity cSt 59.262 verdor.	lowrate	kmol/h	473.300	
emperature C 338.800 ressure (min) kPa (g) -0.500 thialyy MJh -39447.7 W kg/kmole 25.100 lass Density kg/m3 0.500 lass Heat Capacity kJ/kg/k 1.314 hermal Conductivity Wm-K 0.050 mark Vecosity oP 0.029 inematic Viscosity cSt 59.262 inematic Viscosity cSt 59.262 vector C. DRAWINGS AND SKETCHES Vector	lass Flowrate			
ressure (min) kPa (g) -0.500	emperature			
M/h -39447.7 W kg/kmole 25.100 Kas Density kg/m3 0.500 Lass Density kg/kg-K 1.314 Lass Leagacity kJ/kg-K 1.314 Immail Conductivity W/m-K 0.050 ynamic Viscosity cP 0.029 Inematic Viscosity cSt 59.262 Inematic Viscosity CSt 59.262 Inematic Viscosity CSt 59.262 Inematic Viscosity CSt 59.262 Vendor. International Conductivity International Conductivity Y Vendor International Conducti		kPa (g)	-0.500	
Number kg/kmole 25.100 lass Density kg/km3 0.500 lass Heat Capacity kJ/kg/K 1.314 hermal Conductivity W/m-K 0.029 ynamic Viscosity cP 0.029 inematic Viscosity cSt 59.262 version State Conductivity Version y Vendor. 2. DRAWINGS AND SKETCHES Verdor. y Vendor. 2. DRAWINGS AND SKETCHES 2. DRAWINGS AND SKETCHES y Vendor. 3. NOTES 2. DRAWINGS AND SKETCHES 2. DRAWINGS AND SKETCHES y Vendor 3. NOTES 2. DRAWINGS AND SKETCHES 2. DRAWINGS AND SKETCHES y Vendor 3. NOTES 2. DRAWINGS AND SKETCHES 2. DRAWINGS AND SKETCHES y Vendor Will Include references. <t< td=""><td></td><td></td><td></td><td></td></t<>				
lass Density kg/m3 0.500 ass Heat Capacity kd/kg-K 1.314 bernal Conductivity W/m-K 0.055 ynamic Viscosity oP 0.029 inematic Viscosity CSt 59.262				
lass Heat Capacity kJkg-K 1.314 hermal Conductivity W/m-K 0.055 inematic Viscosity cP 0.029 inematic Viscosity cS1 59.262		-		 _
hermal Conductivity W/m·K 0.050 ynamic Viscosity cP 0.029 inematic Viscosity cSt 99.262	-	-		 _
ynamic Viscosity cSt 0.029 inematic Viscosity St 0.029 St 0.029		5		
inematic Viscosity oSt 59.262	-			
2. DRAWINGS AND SKETCHES				
y Vendor. y Vendor.	inematic viscosity	cSt	59.262	
y Vendor. y Vendor.				
y Vendor. J NOTES To be confirmed by vendor To be confirmed by Vendor. Vendor will include references.				
y Vendor. J NOTES To be confirmed by vendor To be confirmed by Vendor. Vendor will include references.				
y Vendor. J NOTES To be confirmed by vendor I To be confirmed by Vendor. Vendor will include references.		2. DRAWINGS AND S	SKETCHES	
S. NOTES 1 To be confirmed by vendor 1 Tybical configuration. To be confirmed by Vendor. 1 Yendor will include spare parts and consumables for 2 years operation. V Vendor will include references.	y Vendor.			
) To be confirmed by vendor	,			
) To be confirmed by vendor				
) To be confirmed by vendor				
) To be confirmed by vendor				
) To be confirmed by vendor				
) To be confirmed by vendor				
) To be confirmed by vendor				
) To be confirmed by vendor				
) To be confirmed by vendor				
) To be confirmed by vendor				
) To be confirmed by vendor				
) To be confirmed by vendor				
) To be confirmed by vendor				
) To be confirmed by vendor				
) To be confirmed by vendor				
) To be confirmed by vendor				
) To be confirmed by vendor				
) To be confirmed by vendor				
) To be confirmed by vendor				
) To be confirmed by vendor				
) To be confirmed by vendor				
) To be confirmed by vendor				
) To be confirmed by vendor				
) To be confirmed by vendor				
) To be confirmed by vendor				
) To be confirmed by vendor				
) To be confirmed by vendor				
) Typical configuration. To be confirmed by Vendor.) Vendor will include spare parts and consumables for 2 years operation.) Vendor will include references.				
) Vendor will include spare parts and consumables for 2 years operation.) Vendor will include references.		3. NOTES		
) Vendor will include references.				
		d by Vendor.		
) Typical configuration. To be confirmed	d by Vendor.		
	 Pypical configuration. To be confirmed Vendor will include spare parts and confirmed Vendor will include references. 	d by Vendor. onsumables for 2 years operation.		
) Typical configuration. To be confirmed) Vendor will include spare parts and co) Vendor will include references.	d by Vendor. onsumables for 2 years operation.		
) Typical configuration. To be confirmed) Vendor will include spare parts and co) Vendor will include references.	d by Vendor. onsumables for 2 years operation.		